



# Precision Parts Bearing Co., Ltd.



## SKF FYRP 2.1/2 H Flange Block Bearings

Bearing No. FYRP 2.1/2 H

FYRP 2.1/2 H Bearing 2D drawings and 3D CAD models

Category	Flange Block Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	6.13
EAN	7316576664687
Product Group	M06288
Number of Mounting Holes	4
Mounting Method	Concentric Collar
Housing Style	4 Bolt Round Flange Cartridge
Rolling Element	Spherical Roller Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	1/2 Inch
Relubricatable	Yes
Insert Part Number	22213
Seals	Trigard
Housing Configuration	1 Piece Solid
Pilot Configuration	With Pilot
Inch - Metric	Inch
Long Description	4 Bolt Round Flange Cartridge; 2-1/2" Bore; 6-1/2" Bolt Circle; 4.6" Bolt Spacing; 1 Piece Solid; Concentric Collar Mount; Cast Iron; Spherical Roller Bearing; 3-3/8" Length Thru B



## Precision Parts Bearing Co., Ltd.

Other Features	Double Row   Heavy Duty   Open End   With Set Screw
Category	Flange Block
UNSPSC	31171501
Harmonized Tariff Code	8483.20.40.80
Noun	Bearing
Keyword String	Flanged
Manufacturer URL	<a href="http://www.skf.com">http://www.skf.com</a>
Manufacturer Item Number	FYRP 2.1/2 H
Weight / LBS	13.5
d	2.5 Inch   63.5 Millimeter
Cartridge Pilot Depth	1 Inch   25.4 Millimeter
Bolt Spacing	4.6 Inch   117 Millimeter
D	3.375 Inch   85.725 Millimeter
Nominal Bolt Circle Diameter Round	6.5 Inch   165 Millimeter
Cartridge Pilot Diameter	5.5 Inch   139.7 Millimeter
bore diameter:	2-1/2 in
expansion type:	Non-Expansion Bearing (Fixed)
bolt center-to-center length:	6.5000 in
seal type:	Contact/Lip
overall length/diameter:	7.6250 in
overall depth:	3-1/2 in
flange mounting type:	Four-Bolt Piloted
radial dynamic load capacity:	33300 lb
bearing type:	Spherical Roller
radial static load capacity:	41100 lb
housing construction:	Solid Flange Mount
operating temperature range:	Maximum of +110 ° F ° F
bore type:	Round



## Precision Parts Bearing Co., Ltd.

finish/coating:	Uncoated
duty type:	Standard Duty
lubrication type:	Lubrication Fitting
housing material:	Cast Iron
series:	222
locking device:	Set Screw